

4" 2300lpm

MC 560

Positive Displacement Flow Meter



METERS

> Technical Data

Input – Output: 4" x 4" Standard (6" Optionally)

Type of flange: ANSI, Square NPT, BSPF

Flow Rate: 225 – 2250 lpm (60 – 600 gpm)

Standard measure unit: Litres (US Gallon optionally)

Max Pressure: 10.3 bar (150 Psi)

Repeatability: 0.05%

Accuracy: $\pm 0.12\%$ over a range of 5:1

Viscosity Range: 30 to 1,500,000 SSU (1 to 325,000 cps)

Working Temperature: -30°C to $+70^{\circ}\text{C}$

Absolute compatibility with all Veeder Root components



Highlights:

- Lack of internal friction (No metal-to-metal contact)
- Reduced number of parts
- Long lifetime
- Self-lubricating
- Low and easy maintenance
- Low drop pressure between parts
- Simple and robust design
- Bi-directional liquid flow
- Meets Worldwide Weights and Measures Standards
- Repeatability under diverse conditions and products



Advantage

Continuous Accuracy over a wide range of transfer conditions:

- ✓ flow rates
- ✓ pressure rates
- ✓ product temperature variations
- ✓ liquid viscosity

Meters Control Positive Displacement Flow meters offer the ideal solution in a variety of applications, in which transfer of petroleum products is implicated and high accuracy is required.

Meters Control Positive Displacement flow Meters use the long time proven technology of Tri-Rotor and Vane, with no friction due to the precise accuracy tolerances of the principle.

The **MC** Series Flow Meters are designed and engineered in European Union.

TYPICAL APPLICATIONS

Check of loading / unloading operations of fuel and petrochemical products in fuel bulk plants and/or refineries

On truck tanker for fuel transport and delivery

Heavy duty fuel dispensing system for big vehicles and airplanes

NETMILL Co Ltd

SUITE 38-40 LONDON FRUIT EXCHANGE
BRUSHFIELD ROAD
LONDON E 1 6 EU - UK
T: +44 7552956089

NETMIL TRADING Ltd

2 SOFOULI STR.
8TH FLOOR FLAT 803 CHANTECLAIR Bld.
P.C.:1096 NICOSIA CYPRUS
T: +357 97773504

WEB: www.meterscontrol.com

SALES: sales@eterscontrol.com

TECHNICAL: tech@eterscontrol.com

